


**Features and Benefits**

- Superior thermal performance
- 3.2 W/m-K thermal conductivity
- Electrically isolating
- RoHS compliant
- Halogen-free



**Typical Applications**

- Notebook Computers
- Handheld Portable Electronics
- Micro Heat Pipe assemblies
- Micro Processors, Memory Chips and Graphic Processors
- Motor Control
- Wireless Communication Hardware

**Optional Configurations**

- Can be die-cut into other dimensions

OP-8500 Spec 08 offers good thermal performance and conformability. This material conforms to surface irregularities under low application pressures. It is electrically non-conductive and naturally tacky. Additional adhesive is generally not required.

The proprietary formulation of OP-8500 Spec 08 is RoHS compliant and halogen-free, providing extra reassurance in applications where hazardous substances are forbidden.


Properties	OP-8500 Spec 08	Test Method
Construction & Composition	Soft silicone elastomer	—
Color	Violet	Visual
Thickness Range /inch (mm)	0.02"~0.40" (0.508~10.16) in 0.01" (0.254) increments	—
Standard Sheet Size	12" x 16"	—
Density /g.cm <sup>-3</sup>	3.1	—
Hardness /Shore 00	15	ASTM D2240
UL Flammability Rating	Conforms to UL94 V0 standard	—
Temperature Range /°C	-40°C~200°C	—
Thermal Conductivity/W.m <sup>-1</sup> .K <sup>-1</sup>	3.2	ASTM D5470 (modified)
Breakdown Voltage /V	>4000 (Thickness = 0.02~0.04") >6000 (Thickness ≥ 0.04")	ASTM D149
Volume Resistivity /ohm.cm	8.0 x 10 <sup>13</sup>	ASTM D257
Dielectric Constant @ 1000Hz	12.8	ASTM D150
Shelf Life /Months	24	—

Please contact us for other special requirements

Carrier Treatment	Criteria
Fiber Glass (FG)	Compulsory for ≤ 0.03" (0.75mm)
Rubberized Cloth (RC)	Not Recommended
Pressure Sensitive Adhesive (PSA)	Not Recommended
Detachable Adhesive (DA)	Optional to ≥ 0.039" (1.0mm)
Aluminum Foil (AL)	Optional to ≥ 0.039" (1.0mm)
Kapton (PI)	Not Recommended
Talc treatment (DAT)	Optional to all thickness

**Product Code and Descriptions**

OP 85 XX Spec 08 -XX -XX -XX -XX



**Dimensions**  
SS = Standard sheet size  
**Release Liner**  
ST = Standard  
OT = Other  
**PSA**  
A1 = One side  
A2 = Both sides  
OT = Other  
**Carrier**  
FG = Fiberglass  
AL = Aluminum foil  
CB = Combination  
OT = Other  
**Spec 08 = Special Derivative #**  
**Thickness (mil)**  
00 = Custom thickness  
04 = 40mil  
**85 = 8500 Series**  
**OP = OPTIM™ gap filler**

**SEM (North America) Inc.**

Tel: +1 585-643-2000  
Fax: +1 585-427-7216  
Address: 1555 Jefferson Road,  
Rochester, NY 14623

**SEM Belgium bv**

+32 59 560 270  
Schatting 73,  
8210 Zedelgem, Belgium



**SEM Asia Ltd.**

+852 2686 8168  
+852 2686 8268  
Unit 1, 3/F Block A, New Trade Plaza,  
6 On Ping Street, Shatin, N.T., Hong Kong

**SEM (Dongguan) Ltd.**

+86-769-8334 1628  
+86-769-8334 2028  
No. 8A Qiaoxin Road, Qiaotou,  
Dongguan, Guangdong, China  
Postal code 523525

Specifications and appearances may change without notice. All statements, technical information and recommendations herein are based on tests that we believed to be reliable, but the accuracy and completeness are not guaranteed. Before using, user should determine the suitability of the product for its intended use, and the user assumes all risks and liabilities whatsoever in connection therewith. Neither the seller nor the manufacturer shall be liable for any loss or damage, direct, incidental or consequential, including loss of profits or revenues arising from the use or inability to use the product. Any statements or recommendations shall have no effect unless contained in an agreement signed by authorized personnel of the seller and manufacturer.



**SEM (North America) Inc.**

Tel: +1 585-643-2000  
 Fax: +1 585-427-7216  
 Address: 1555 Jefferson Road,  
 Rochester, NY 14623

**SEM Belgium bv**

+32 59 560 270  
 Schatting 73,  
 8210 Zedelgem, Belgium

**SEM Asia Ltd.**

+852 2686 8168  
 +852 2686 8268  
 Unit 1, 3/F Block A, New Trade Plaza,  
 6 On Ping Street, Shatin, N.T., Hong Kong

**SEM (Dongguan) Ltd.**

+86-769-8334 1628  
 +86-769-8334 2028  
 No. 8A Qiaoxin Road, Qiaotou,  
 Dongguan, Guangdong, China  
 Postal code 523525

Specifications and appearances may change without notice. All statements, technical information and recommendations herein are based on tests that we believed to be reliable, but the accuracy and completeness are not guaranteed. Before using, user should determine the suitability of the product for its intended use, and the user assumes all risks and liabilities whatsoever in connection therewith. Neither the seller nor the manufacturer shall be liable for any loss or damage, direct, incidental or consequential, including loss of profits or revenues arising from the use or inability to use the product. Any statements or recommendations shall have no effect unless contained in an agreement signed by authorized personnel of the seller and manufacturer.